



Designed and Manufactured by NOX Corporation

**Design Center & Office**

KD Center, 355, Hyoryeong-ro, Seocho-gu, Seoul, 06643 Korea  
 Tel +82-2-520-7600  
 Fax +82-2-598-9674  
 www.noxglobal.com  
 E-mail info@noxglobal.com

**NOX Corp. | KOREA**

Shinho Factory  
 Shinho 2nd Factory, Yedang  
 Enbo Factory  
 Godeok Factory  
 Bongsan Factory  
 Deoksan Factory  
 Choongnam, Korea

**NOX US | USA**

NOX US  
 P.O. Box 824  
 931 S. Springville Avenue  
 Fostoria, OH 44830  
 Office +01-419-701-5060  
 Fax +01-419-701-5058

**HERRINGBONE**  
 Classic & Cozy



LOOM+  
DIFFERENCE

# LOOM+ DIFFERENCE

DESIGN AND TECHNOLOGY  
ARE WOVEN TOGETHER

## Infinite DESIGN spectrum


Only LOOM+ enables unique variation of creating your own floor by mixing and matching different patterns in two tile sizes.

## Distinguished NOX EMT™ Core Structure

The first woven flooring with proven NOX EMT™ core structure that ensures the most stable and durable installation.

# LOOM+ DESIGN

PLAY with COLOR, SIZE and TEXTURE



## Profound Color Composition

Realizing multiple tones of color - carefully selected by artists - we provide you with very unique colors that expresses LOOM+ in harmony with surrounding interiors.



## Infinite array of color and texture

Available in 59 colors covering diverse tones like neutral, cool, warm, light, and dark in five different yarn thicknesses, we give you nine unique design patterns.



## Designed for mix & match

Creative and unique 'mix & match' only by LOOM+ is realized by introducing the same weaving system to nine design patterns.



50x50cm  
Standard size



25x100cm  
Plank size

## Optimal 2 Size variation

With our unique 2 module sizes of 50cmx50cm and 25cmx100cm, the first introduced in woven flooring market, you can elevate the flat environments to inspiring interior spaces.

# LOOM+ TECHNOLOGY

PROVEN INNOVATION



## Distinguished NOX EMT™ Core Structure

NOX EMT™ core structure featured with innovative functionality and safety, proven in more than 50 countries over 20 years



### Clean & Tough



- + The first & only in woven flooring with NOX EPT™ shield treatment (Anti-Bacterial)
- + Strong enough for heavy commercial use

### Dimensional Stability & Consistent Thickness



- + The most reliable NOX EMT™ core structure
- + Consistent product thickness by patterns for mix & match with different patterns

### Fray-Proof



- + Clean-cut finishing for preventing fraying even when cutting tiles during installation



### Safe

Certified non-toxic, phthalate-free, and fiberglass-free fabric



### Quick

Quick and Easy ECOLAY® installation without glue



### Easy

Minimal cleaning time and low maintenance



### Silent & Soft

Soft surface absorbing sound



### Non-Slip

Slip-resistance with woven fabric surface




### Colorfast

Colorfast properties retain gorgeous original colors over time


# HERRINGBONE

Classic & Cozy


NOX Herringbone collection offers versatility using cool and warm natural accent tones to create artistic design and comfort in any room. Offered in our new 25cmx100cm plank format, providing a rustic appearance when installed in an ashlar paving pattern.




FQ-2501




FQ-2502




FQ-2503



FQ-2504



FQ-2505



FQ-2506

Reinvent Spaces with


# LOOM<sup>+</sup> PLAY!

New 25cmx100cm MIXMATCH plank brings new proportion and scale to your flooring to create fresh and exciting designs. In addition to new MIXMATCH plank, LOOM<sup>+</sup> modular system includes 50cmx50cm squares.

All work together in any combination, giving you the freedom to create your own design by mixing & matching different patterns and colors in 2 size variations.




50x50cm




25x100cm


## INSTALLATION CONCEPT GUIDE




LOOM PLAY #1




LOOM PLAY #2




LOOM PLAY #3




LOOM PLAY #4




LOOM PLAY #5




LOOM PLAY #6




LOOM PLAY #7




LOOM PLAY #8




LOOM PLAY #9




LOOM PLAY #10




LOOM PLAY #11




LOOM PLAY #12




LOOM PLAY #13




LOOM PLAY #14




LOOM PLAY #15




LOOM PLAY #16




LOOM PLAY #17



LOOM PLAY #18




LOOM PLAY #19




LOOM PLAY #20


## NEW LOOM<sup>+</sup> PLAY!




LOOM PLAY #21




LOOM PLAY #22




LOOM PLAY #23




LOOM PLAY #24




LOOM PLAY #25




LOOM PLAY #26




LOOM PLAY #27




LOOM PLAY #28




LOOM PLAY #29




LOOM PLAY #30




LOOM PLAY #21




LOOM PLAY #22




LOOM PLAY #23




LOOM PLAY #24




LOOM PLAY #25




LOOM PLAY #26




LOOM PLAY #27



LOOM PLAY #28



LOOM PLAY #29




LOOM PLAY #30

Residential

GLOBAL  
REFERENCES

**LOOM**<sup>+</sup>  
CREATE  
YOUR OWN DESIGN

FQ-2501 FQ-2502




LOOM PLAY #22

Restaurant



FQ-2502 FQ-2503  
FQ-2505




LOOM PLAY #21

Corporate



FQ-2501 FQ-2502  
FQ-2506




LOOM+ PLAY  
MIX&MATCH

Retail shop



FQ-2501 FQ-2505  
FQ-2506




LOOM PLAY #21

Hospitality



FQ-2503




LOOM PLAY #24



Education & Libraries



FQ-2501 FQ-2502  
FQ-2505 FQ-2506




LOOM PLAY #27

Healthcare




FQ-2502 FQ-2503  
FQ-2504 FQ-2505



LOOM PLAY #25

## Sports Center



LOOM PLAY #26

FQ-2501 FQ-2502  
FQ-2505

## TECHNICAL INFORMATION

### 1. Size & Packing

Size(mm)	Thickness(mm)	Pcs/Box	m <sup>2</sup> /Box	Kg/m <sup>2</sup>
500x500	3	16 pcs/box	4 m <sup>2</sup>	5.0
	5	10 pcs/box	2.5 m <sup>2</sup>	8.2
250x1000	3	16 pcs/box	4 m <sup>2</sup>	5.0
	5	10 pcs/box	2.5 m <sup>2</sup>	8.2

### 2. Test Result

Test Item		Standard	LOOM <sup>+</sup>
Level of use		EN 685	33
Fraying		EN 1814	Frayproof
Thermal resistance		ISO 8302	0.02m <sup>2</sup> K/W
Castor chair resistance		EN 985	No damage
Dimensional stability		ISO 23999 EN 986	≤ 0.10% ( Norm: ≤ 0.25% ) Passed
Fire resistance		EN 13501-1	Bfl -s1
Indoor air quality			Low VOC (floor score certified)
Underfloor heating		EN 12524	Suitable
Light fastness		ISO 105-B02	≥ 6
Slip resistance		DIN 51130 EN 13893	R11 DS
Flexibility		ISO 24344	Passed
Impact sound insulation		ISO 10140-3	9dB
Body Voltage		EN 1815	≤ 2KV
Squareness & Straightness		ISO 24342 ASTM F2055	No deviation ≤ 0.01 in
Residual indentation		ISO 24343-1 ASTM F1914	≤ 0.1mm < 8%
Resistance to chemicals		ISO 26987 ASTM F925	No Defects No Defects

### 3. Caution

Condition in at least 19°C or the normal temperature of the room where the product is to be laid, for at least 48 hours before installing. Cartons must be stacked less than 5 high and tiles removed 30 minutes before use. The site conditions must be maintained during installation and for at least 48 hours after completion. NOX Corporation will not accept claims where these instructions have not been followed.

### 4. Certificate



Visit [www.loomplus.com](http://www.loomplus.com) for the detailed installation / maintenance guides and technical information.